



# Model 935-E

## End-of-Line Breather Vent with Integrated Flame Arrester

BSBflamearrester.com | BSBsystems.com

Visit our website for the most complete, up-to-date information

Drawing on extensive experience in the pressure relief field, the BS&B FlameSaf® pressure relief vent with integrated flame arrester offers a dependable, internationally certified and precisely engineered design to prevent excessive pressure build-up and rupture of valuable tankage during overpressure situations. The valve, which include an integral flame arrester, positioned to minimize plugging, along with a light-weight, compact design, are expertly engineered to respond to even minimal changes in pressure. Fully opening at pressure rises of just 10% overpressure, enabling users to optimize operating conditions close to limits while ensuring reliable operation that safeguards personnel and the environment. Consult your local BS&B representative or call us for consultation on your safety concerns.

### Features

- End-Of-Line Breather Vent with Integrated Flame Arrester
- Pressure Vent: Deflagration proof
- EC prototype test certificate according to ATEX Directive 2014/34/EU and EN ISO 16852:2016, EN 13463-1 and EN 13463-5
- Available in nom. Diameter: DN50 (2"), DN80 (3")

### Protection

- Gas/air or vapour/air-mixtures for explosion groups up to and including IIB3 (NEC Group D), MESH  $\geq 0.65$ mm

### Connection Type

- ISO 7005 PN10
- ANSI B16.5 – 150 RF
- Other types available upon request



Model 935-E End-Of-Line Breather Vent with Integrated Flame Arrester

Materials of Construction				
	Stainless Steel	Hastelloy	Ductile Iron	Other Materials on request
Metal Foil Element	✓	✓		✓
Housing of Metal Foil Element	✓	✓		✓
Body / Cover	✓		✓	✓
<i>Painting Options Available</i>				

EC Type Examination	
Designation	935-E 50 to 80
Protective System	Pressure vent with integrated flame arrester for explosion groups up to and including IIB3 (NEC Group D)
Compliance with guidelines:	ATEX 2014/34/EU EN ISO 16852:2016

**Limerick, Ireland**  
T: +353 61 517000  
F: +353 61 309689  
E: info@bsbflamearrester.ie

**Düsseldorf, Germany**  
T: +49 211 930550  
F: +49 211 3982171  
E: info@bsbsystems.de

**Houston, TX USA**  
T: +1 713 682 4515  
F: +1 713 682 5992  
E: sales@bsbsystems.com

**Seoul, Korea**  
T: +82 2 3782 4591  
F: +82 2 3782 4555  
E: sales@bsbsystems.kr

**Den Haag, Netherlands**  
T: +31 70 362 2136  
F: +31 70 360 4724  
E: info@bsbsystems.nl

**Manchester, UK**  
T: +44 0 161 955 4202  
F: +44 0 161 870 1086  
E: sales@bsb-systems.co.uk

**Moscow, Russia**  
T: +7 495 747 5916  
F: +7 499 133 4394  
E: sales@bsbsystems.ru

**Shanghai, China**  
T: +86 21 6391 2299  
F: +86 21 6391 2117  
E: sales@bsbsystems.com

*Products, specifications and all data in this literature are subject to change without notice. Questions regarding product selection and specifications for specific applications should be directed to BS&B. All sales are subject to the BS&B companies' standard terms and conditions of sale. Nothing herein should be construed as a warranty of merchantability or fitness for a particular purpose.*